


## Product information sheet

Product number: 0432412241

Date: 18.04.2026

Page: 1/2



## DC-DC Converter PV24i 24-12 V/24 A

DC-DC converter, galvanically insulated, with 24 V input voltage to 12 V output voltage in compact switched-mode technology, lightweight, shock and vibration resistant with IP53.

- // Compact switched-mode technology
- // Shake and vibration-resistant
- // Galvanically insulated

The galvanically insulated DC-DC converter of the PV series easily converts a 24 V on-board power supply voltage into a steady 12 V on-board power supply voltage. The devices in the PV series are characterised by their compact dimensions, low weight and high efficiency.

The DC-DC converter is attached with a practical mounting clip, which makes installation easy and minimises installation time. A green LED indicates the operating status of the DC-DC converter.

## Product information sheet

Product number: 0432412241

Date: 18.04.2026

Page: 2/2



## Technical Information

Galvanically isolated	Yes*
Input voltage (DC)	24 V*
Number of outputs	1*
Output voltage (DC)	12 V*
Power	288 W*
Bias current	< 15 mA
Connector	6.3 mm flat push-on connection
Input voltage range	17 ... 32 V
International Protection (IP class)	IP53
Level of efficiency	> 85 %
Operating temperature	-25 °C ... +30 °C
Output current	24 A
Dimensions (L x W x H)	50 x 217 x 87 mm
Weight	0.85 kg

\*In the chosen option